Tabletop Laminators

Big Profits from a Compact Laminator!

Royal Sovereign tabletop roll laminators provide high quality performance in a compact space efficient design that is ideal for any small Sign or Print Shop. Combine these laminators with a graphics printer to provide endless finishing solutions.

Royal Sovereign Advantages

- Easy to Use Simple set-up with one button operation and soft touch digital controls on the front of the laminator
- Optimized Performance Perfect for use by schools and most print and sign shops
- **Compact Design** Designed with a small footprint for use in tight work spaces
- Fast Laminating Short warm-up times and quick motor speeds provide for fast finishing



Royal Sovereign's tabletop roll laminators are a great fit for print shops, sign shops, and schools. Built for safety and ease of use, these sturdy machines have durable, sturdy frame construction and require little assembly and minimal maintenance. Enhanced features and functions make laminating easier than ever. Perfect for laminating documents, posters, placemats, letters, art work, training aids, and various educational materials up to 27" wide. Backed by over 30 years of experience, these economically priced tabletop roll laminators are a smart option for today's schools, print & sign shops.

Tabletop Laminators Specifications







Film Thickness1mil - 5mil*1.5 mil - 5mil1mil - 5mil*Max Laminating Speed8.2ft/min.7.9ft/min.14.8ft/min.Speed Control9 Settings10 Settings9 SettingsTransport Type4 Rollers4 Rollers4 RollersHeating Type (2 Rollers)Hot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 Rollers2 RollersPull Rollers10 minutes10 minutes8 minutesReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-Grips2.25" & 3" Auto-GripsFilm Core SizeYesYesYesReverseYesNoNoReverseYesNoNoHot LaminationYesNoNoHot LaminationYesNoYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight	MODEL	RSL-2702S	RSL-2701	RSH-380SL
Film Thickness1mil - 5mil*1.5 mil - 5mil1mil - 5mil*Max Laminating Speed8.2ft/min.7.9ft/min.14.8ft/min.Speed Control9 Settings10 Settings9 SettingsTransport Type4 Rollers4 Rollers4 RollersHeating Type (2 Rollers)Hot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 Rollers2 RollersPull Rollers10 minutes10 minutes8 minutesReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-GripsFilm Core SizeYesYesYesReverseYesYesYesCold LaminationYesNoNoHot LaminationYesNoYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W120WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)<				
Max Laminating Speed8.2ft/min.7.9ft/min.14.8ft/min.Speed Control9 Settings10 Settings9 SettingsTransport Type4 Rollers4 Rollers4 RollersHeating Type (2 Rollers)Hot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 Rollers2 RollersReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-Grips1" Core Plug &2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core Plug(1" Core Plug Option)ReverseYesYesYesYesCold LaminationYesYesYesEncapsulationYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety SystemSafety CoverSafety CoverSafety CoverMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzDimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs133 lbs101 lbs.	Maximum Laminating Width	27"	27"	15"
Speed Control9 Settings10 Settings9 SettingsTransport Type4 Rollers4 Rollers4 Rollers4 RollersHeating Type (2 Rollers)Hot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 RollersReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-Grips1" Core Plug(1" Core Plug Option)ReverseYesYesYesYesCold LaminationYesYesYesYesBrandationYesYesYesYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"	Film Thickness	1mil - 5mil*	1.5 mil - 5mil	1mil - 5mil*
Transport Type4 Rollers4 Rollers4 Rollers4 RollersHeating Type (2 Rollers)Hot RollersHot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 Rollers2 RollersReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-Grips2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core Plug (1" Core Plug Option)ReverseYesYesYesCold LaminationYesYesYesSingle-Sided LaminationYesYesYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WXDXH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"	Max Laminating Speed	8.2ft/min.	7.9ft/min.	14.8ft/min.
Heating Type (2 Rollers)Hot RollersHot RollersHot RollersPull Rollers2 Rollers2 Rollers2 Rollers2 RollersReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core Plug(1" Core Plug Option)ReverseYesYesYesCold LaminationYesYesYesHot LaminationYesYesYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzDrive Motor1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Speed Control	9 Settings	10 Settings	9 Settings
Pull Rollers2 Rollers2 Rollers2 RollersReady Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core PlugReverseYesYesYesCold LaminationYesNoNoHot LaminationYesYesYesSingle-Sided LaminationYesNoYesMemory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Transport Type	4 Rollers	4 Rollers	4 Rollers
Ready Time10 minutes10 minutes8 minutes1" Core Plug &2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core Plug(1" Core Plug Option)ReverseYesYesYesYesCold LaminationYesNoNoHot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Drive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Heating Type (2 Rollers)	Hot Rollers	Hot Rollers	Hot Rollers
1" Core Plug &2.25" & 3" Auto-GripsFilm Core Size3" Auto-Grip1" Core Plug(1" Core Plug Option)ReverseYesYesYesYesCold LaminationYesNoNoHot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoNoMemory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.		2 Rollers	2 Rollers	2 Rollers
Film Core Size3" Auto-Grip1" Core Plug(1" Core Plug Option)ReverseYesYesYesCold LaminationYesNoNoHot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Ready Time	10 minutes	10 minutes	•
ReverseYesYesYesYesCold LaminationYesNoNoHot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoYesMemory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.		1" Core Plug &		2.25" & 3" Auto-Grips
Cold LaminationYesNoNoHot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoYesMemory SettingsYesNoYesDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Film Core Size	3" Auto-Grip	1" Core Plug	(1" Core Plug Option)
Hot LaminationYesYesYesEncapsulationYesYesYesSingle-Sided LaminationYesNoYesMemory SettingsYesNoYesDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Reverse	Yes	Yes	Yes
EncapsulationYesYesYesSingle-Sided LaminationYesNoYesMemory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety SystemSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Cold Lamination		No	No
Single-Sided LaminationYesNoYesMemory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety System302° F302° F302° FMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Hot Lamination	Yes	Yes	Yes
Memory SettingsYesNoNoDe-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety System302° F302° F302° FMaximum Temperature302° F302° F302° FMaximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Encapsulation	Yes	Yes	Yes
De-Curl DeviceYesNoYesSafety SystemSafety CoverSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Single-Sided Lamination	Yes	No	Yes
Safety SystemSafety CoverSafety CoverSafety CoverSafety CoverMaximum Temperature302° F302° F302° FMaximum Film Diameter7.8"4.7"7.8"Maximum Mounting Thickness.24".08".24"Rear Cross CutterYesYesYesDrive MotorDC GearedDC GearedDC GearedVoltage120V / 60Hz120V / 60Hz120V / 60HzPower Consumption1500W1450W1200WUnit Weight154 lbs.110 lbs.91 lbs.Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Memory Settings		No	No
Maximum Temperature 302° F 302° F 302° F 302° F Maximum Film Diameter 7.8" 4.7" 7.8" Maximum Mounting Thickness .24" .08" .24" Rear Cross Cutter Yes Yes Yes Drive Motor DC Geared DC Geared DC Geared Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	De-Curl Device	Yes	No	Yes
Maximum Film Diameter 7.8" 4.7" 7.8" Maximum Mounting Thickness .24" .08" .24" Rear Cross Cutter Yes Yes Yes Drive Motor DC Geared DC Geared DC Geared Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 120W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Safety System		Safety Cover	
Maximum Mounting Thickness .24" .08" .24" Rear Cross Cutter Yes Yes Yes Drive Motor DC Geared DC Geared DC Geared Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	-			
Yes Yes Yes Drive Motor DC Geared DC Geared DC Geared Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Maximum Film Diameter			
Drive Motor DC Geared DC Geared DC Geared Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Maximum Mounting Thickness	.24"	.08"	.24"
Voltage 120V / 60Hz 120V / 60Hz 120V / 60Hz 120V / 60Hz Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Rear Cross Cutter			Yes
Power Consumption 1500W 1450W 1200W Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Drive Motor			
Unit Weight 154 lbs. 110 lbs. 91 lbs. Dimensions (WxDxH) 38" x 22" x 19" 36" x 21" x 13" 25" x 22" x 18" Carton Weight 176 lbs. 133 lbs. 101 lbs.	Voltage	-		•
Dimensions (WxDxH)38" x 22" x 19"36" x 21" x 13"25" x 22" x 18"Carton Weight176 lbs.133 lbs.101 lbs.	Power Consumption			
Carton Weight 176 lbs. 133 lbs. 101 lbs.	Unit Weight			
	Dimensions (WxDxH)	38" x 22" x 19"	36" x 21" x 13"	25" x 22" x 18"
Carton Dimensions (WxDxH) 45" x 24" x 24" 45" x 29" x 21" 29" x 32" x 26"	Carton Weight			
	Carton Dimensions (WxDxH)	45" x 24" x 24"	45" x 29" x 21"	29" x 32" x 26"

*10 mil lamination possible on RSH-380SL & RSL-2702S for short duration at high temperature